




TO-263 Plastic-Encapsulate MOSFETS

CCM03N120

N-Channel Power MOSFET

V _{DS}	R _{DS(ON)} (Typ.)	I _D
1200 V	6.7Ω@10V	3A



DESCRIPTION

The CCM03N120 provides excellent R_{DS(ON)} with low gate charge. It can be used in a wide variety of applications.


FEATURES

- RoHS Compliant
- Low ON Resistance
- Low Gate Charge
- Peak Current vs Pulse Width Curve
- Inductive Switching Curves
- AEC Q101 Qualified

APPLICATIONS

- SMPS
- Adaptor
- Electric welder


MARKING



CCM03N120 =Part No.

XXXXXXXX = Code

EQUIVALENT CIRCUIT



ABSOLUTE MAXIMUM RATINGS($T_c=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	1200	V
Gate-Source Voltage	V_{GS}	± 30	V
Continuous Drain Current $T_c=25^{\circ}\text{C}$	I_D	3	A
Continuous Drain Current $T_c=125^{\circ}\text{C}$	I_D	1.8	A
Pulsed Drain Current ¹	I_{DM}	12	A
Single Pulse Avalanche Energy ²	EAS	31	mJ
Total Power Dissipation	P_D	120	W
Thermal Resistance from Junction to Case ³	$R_{\theta JC}$	1.25	$^{\circ}\text{C}/\text{W}$
Thermal Resistance from Junction to Ambient ⁴	$R_{\theta JA}$	120	$^{\circ}\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~ +175	$^{\circ}\text{C}$
Soldering Temperature , for 10S(1.6mm from case)	-	260	$^{\circ}\text{C}$

Notes:

- 1.Repetitive Rating: Pulse width limited by maximum junction temperature.
- 2.Start $T_J = 25^{\circ}\text{C}$, $L = 10\text{mH}$, $I_{AS} = 2.5\text{A}$, $V_{GS} = 10\text{V}$.
- 3.Water cooled heatsink, P_D adjusted for a peak junction temperature of 175°C .
- 4.1 cubic foot chamber, free air.

MOSFET ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise specified


Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	1200			V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 1200V, V_{GS} = 0V, T_J = 25^\circ C$		1.18	5	μA
		$V_{DS} = 1200V, V_{GS} = 0V, T_J = 125^\circ C$		1.7	10	
		$V_{DS} = 1200V, V_{GS} = 0V, T_J = 175^\circ C$		35	50	
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 30V, V_{DS} = 0V$			± 100	nA
On characteristics ¹						
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	3	3.7	5	V
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 1.5A$		6.7	9	Ω
Transconductance	gfs	$V_{DS} = 15V, I_D = 1.5A$		3.8		S
Dynamic characteristics						
Input Capacitance	C_{iss}	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$		865		μF
Output Capacitance	C_{oss}			59		
Reverse Transfer Capacitance	C_{rss}			6.6		
Gate resistance	R_g	$V_{GS} = 0V, V_{DS} = 0V, f = 1MHz$		4		Ω
Switching characteristics						
Total Gate Charge	Q_g	$V_{DD} = 960V, V_{GS} = 10V, I_D = 3A$		19.7		nC
Gate-Source Charge	Q_{gs}			7.5		
Gate-Drain Charge	Q_{gd}			5.4		
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 600V, V_{GS} = 10V, I_D = 3A, R_G = 10\Omega$		15.1		ns
Turn-on rise time	t_r			19.4		
Turn-off delay time	$t_{d(off)}$			25.6		
Turn-off fall time	t_f			76.2		
Drain-source Diode characteristics ¹						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0V, I_{SD} = 3A, T_J = 25^\circ C$			1.5	V
Continuous Source Current	I_S	$T_C = 25^\circ C$			3	A
Pulsed drain-source diode forward current	I_{SM}	—			12	A
Reverse recovery time	T_{rr}	$I_F = 3A, di/dt = 100A/\mu s$		526		ns
Reverse recovery charge	Q_{rr}				2000	

Note :


1. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

Typical Characteristics


PD -- Tc




ID -- Tc




ID -- VDS




ID -- VGS




RDS(on) -- ID




IS -- VSD




RDS(on) -- VGS




Threshold Voltage




Drain-source breakdown voltage




RDS (on) -- Tj




Typ.gate charge




Avalanche energy




Typ. capacitance




Gate charge waveforms




Maximum Forward Biased Safe Operating Area



Normalized Thermal Transient Impedance




TO-263-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.470	4.670	0.176	0.184
A1	0.000	0.150	0.000	0.006
B	1.120	1.420	0.044	0.056
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.310	0.530	0.012	0.021
c1	1.170	1.370	0.046	0.054
D	10.010	10.310	0.394	0.406
E	8.500	8.900	0.335	0.350
e	2.540 TYP.		0.100 TYP.	
e1	4.980	5.180	0.196	0.204
L	14.940	15.500	0.588	0.610
L1	4.950	5.450	0.195	0.215
L2	2.340	2.740	0.092	0.108
L3	1.300	1.700	0.051	0.067
Φ	0°	8°	0°	8°
V	5.600 REF.		0.220 REF.	

TO-263-2L Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: 0.5mm.
3. The pad layout is for reference purposes only.


NOTICE

Cloudchild reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Cloudchild does not assume any liability arising out of the application or use of any product described herein.

ChongQing Cloudchild Technology Co., Ltd. (short for Cloudchild) exerts the greatest possible effort to ensure high quality and reliability. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing Cloudchild products, to comply with the standards of safety in making a safe design for the entire system, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue. In developing your designs, please ensure that Cloudchild products are used within specified operating ranges as set forth in the most recent Cloudchild products specifications.

TO-263-2L Tape and Reel

TO-263-2L Embossed Carrier Tape




Packaging Description:

TO-263-2L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 800 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).


Dimensions are in millimeter

Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-263-2L	10,80	16,13	5,21	Ø1,55	1,75	11,50	4,00	16,00	2,00	24,00

TO-263-2L Tape Leader and Trailer



TO-263-2L Reel



Dimensions are in millimeter

Reel Option	D	D1	D2	W1	W2	I
13"Dia	Ø330.00	100.00	Ø21.00	24.4	30.4	Ø13.00

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
800 pcs	13 inch	800 pcs	340×336×36	8,000 pcs	400×353×365	

Date of change	Rev #	revise content
2022/11/22	A/0	/