



**PDFN/PPAK5×6-8L Plastic-Encapsulate MOSFETS**

**CCME100N06S N-Channel Power MOSFET**

$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	$I_D$
60 V	2.6mΩ@10V	100A
	5.5mΩ@4.5V	

**DESCRIPTION**

The CCME100N06S uses advanced SGT technology and design to provide excellent  $R_{DS(ON)}$  with low gate charge. It can be used in a wide variety of applications .


**FEATURES**

- Excellent package for good heat dissipation
- Ultra low gate charge
- Low reverse transfer capacitance
- Fast switching capability
- Avalanche energy specified
- AEC Q101 qualified


**APPLICATIONS**

- 12V/24V Automotive systems
- Motors,lamps and solenoid control
- Transmission control
- Power switching application


**MARKING**



CCME100N06S =Part No.  
 XXXXXXXX = Code.



**EQUIVALENT CIRCUIT**



**ABSOLUTE MAXIMUM RATINGS( $T_c=25^{\circ}\text{C}$  unless otherwise noted)**

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>1</sup>	$I_D$	100	A
Pulsed Drain Current <sup>2</sup>	$I_{DM}$	400	A
Single Pulse Avalanche Energy <sup>3</sup>	EAS	225	mJ
Total Power Dissipation <sup>1</sup>	$P_D$	83	W
Thermal Resistance from Junction to Case <sup>1</sup>	$R_{\theta JC}$	1.8	$^{\circ}\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55~ +175	$^{\circ}\text{C}$
Soldering Temperature , for 10S(1.6mm from case)	-	260	$^{\circ}\text{C}$

**Notes:**

1.  $T_c=25^{\circ}\text{C}$  Limited only by maximum temperature allowed.
2.  $P_w \leq 10\mu\text{s}$ , Duty cycle  $\leq 1\%$ .
3. EAS condition:  $V_{DD}=20\text{V}, V_{GS}=10\text{V}, I_D=30\text{A}, L=0.5\text{mH}, R_g=25\Omega$  Starting  $T_J=25^{\circ}\text{C}$ .

# MOSFET ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise specified


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Off characteristics</b>						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	60			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 60V, V_{GS} = 0V$		0.1	1	$\mu A$
Gate-body leakage current	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$		2	$\pm 100$	nA
<b>On characteristics<sup>4</sup></b>						
Gate-threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	2.5	3.0	V
Static drain-source on-state resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 20A$		2.6	4.8	m $\Omega$
Forward transconductance	$g_{fs}$	$V_{DS} = 10V, I_D = 10A$		50		S
<b>Dynamic characteristics<sup>3,4</sup></b>						
Input capacitance	$C_{iss}$	$V_{DS} = 25V, V_{GS} = 0V,$ $f = 1MHz$		3800		pF
Output capacitance	$C_{oss}$			1358		
Reverse transfer capacitance	$C_{rss}$			76		
Gate resistance	$R_g$	$f = 1MHz$		2.4		$\Omega$
<b>Switching characteristics<sup>3,4</sup></b>						
Total gate charge	$Q_g$	$V_{GS} = 10V, V_{DD} = 48V,$ $I_D = 25A$		70		nC
Gate-source charge	$Q_{gs}$			16		
Gate-drain charge	$Q_{gd}$			21		
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 45V, R_L = 1.8\Omega,$ $V_{GS} = 10V, R_G = 5\Omega$		14		ns
Turn-on rise time	$t_r$			25		
Turn-off delay time	$t_{d(off)}$			55		
Turn-off fall time	$t_f$			28		
<b>Drain-Source Diode Characteristics</b>						
Drain-source diode forward voltage <sup>4</sup>	$V_{SD}$	$V_{GS} = 0V, I_S = 20A$		0.80	1.2	V
Continuous drain-source diode forward Current <sup>1</sup>	$I_S$	-			100	A
Pulsed drain-source diode forward current <sup>2</sup>	$I_{SM}$	-			400	A
Reverse recovery time	$T_{rr}$	$I_F = 20A, di/dt = 100A/\mu s$		32		ns
Reverse recovery charge	$Q_{rr}$				36	

Note :


1.  $T_C = 25^\circ C$  Limited only by maximum temperature allowed.
2.  $P_w \leq 10\mu s$ , Duty cycle  $\leq 1\%$ .
3. Guaranteed by design, not subject to production.
4. Pulse Test : Pulse Width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .

# Typical Characteristics


PD -- Tc




ID -- Tc




ID -- VDS




ID -- VGS




RDS(on) -- ID




Is -- VSD




**RDS(on) -- VGS**




**Threshold Voltage**




**Drain-source breakdown voltage**




**RDS (on) -- TJ**




**Typ.gate charge**




**Avalanche energy**




### Typ. capacitance




### Gate charge waveforms






### Maximum Forward Biased Safe Operating Area



### Normalized Thermal Transient Impedance




# PDFN/PPAK5\*6-8L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
u	10°	12°	10°	12°

# PDFN/PPAK5\*6-8L Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: 0.5mm.
3. The pad layout is for reference purposes only.


## NOTICE

Cloudchild reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Cloudchild does not assume any liability arising out of the application or use of any product described herein.

ChongQing Cloudchild Technology Co., Ltd. (short for Cloudchild) exerts the greatest possible effort to ensure high quality and reliability. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing Cloudchild products, to comply with the standards of safety in making a safe design for the entire system, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue. In developing your designs, please ensure that Cloudchild products are used within specified operating ranges as set forth in the most recent Cloudchild products specifications.

## PDFN/PPAK5\*6-8L Tape and Reel

### PDFN/PPAK5\*6-8L Embossed Carrier Tape




#### Packaging Description:

PDFN/PPAK5\*6-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).


Dimensions are in millimeter

Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFN/PPAK5*6-8L	6.30	5.30	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

### PDFN/PPAK5\*6-8L Tape Leader and Trailer



### PDFN/PPAK5\*6-8L Reel



Dimensions are in millimeter

Reel Option	D	D1	D2	G	W1	W2
13"Da	Ø330,00	100,00	13,00	1,90	17,60	12,40

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
5,000 pcs	13 inch	5,000 pcs	340×336×29	50,000 pcs	353×346×365



Date of change	Rev #	revise content
2022/11/28	A/0	/